



More information on the website
radwag.com/en/info,w1,N0J
























XA 52.5Y.A Analytical Balance



XA 52.5Y.A Analytical Balance

The drawings, photos and graphics used are for illustrative purposes only.

Functions

- | | | | |
|--|---|---|---|
|  Autotest |  Dosing |  Percent Weighing |  Parts counting |
|  Peak hold |  Formulation |  Newton unit measurement |  Statistics |
|  Checkweighing |  IR sensors |  Under-pan weighing |  GLP Procedures |
|  Animal weighing |  Pipettes Calibration |  Air density correction |  Automatic sliding door |
|  Density determination |  Differential weighing |  Ambient conditions monitoring |  Statistical Quality Control |
|  Packaged Goods Control |  ALIBI Memory |  Wi-Fi | |

Datasheet

	XA 52.5Y.A Analytical Balance
Metrological parameters	
Maximum capacity [Max]	52 g
Minimum load	1 mg
Readability [d]	0,01 mg
Verification unit [e]	1 mg
Tare range	-52 g
Standard repeatability [5% Max]	0,005 mg
Standard repeatability [Max]	0,01 mg
Standard minimum weight (USP)	10 mg
Standard minimum weight (U=1%, k=2)	1 mg
Permissible repeatability [5% Max]	0,012 mg
Permissible repeatability [Max]	0,02 mg
Linearity	±0,03 mg
Eccentric load deviation	0,03 mg
Sensitivity time drift	$1 \times 10^{-6} / \text{Year} \times \text{Rt}$
Stabilization time	4 s
Adjustment	internal (automatic)
OIML Class	I
Physical parameters	
Leveling system	automatic - Reflex Level System
Display	10" touchscreen
Weighing chamber	automatic
Weighing chamber doors	automatic
Delivery components	Analytical Balance, weighing pan, weighing pan shield, centring ring, brush, fabric dust cover, power supply.
Weighing chamber dimensions	200×170×220 mm
Weighing pan dimensions	ø90 open-work pan + ø85 (option) mm
Packaging dimensions	750×492×595 mm
Net weight	14,7 kg
Gross weight	20 kg
Communication interface	
Communication interface	USB-A x2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A Balance: 12 – 15V DC 1,6A max*
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0,3°C/1h (±1°C/8h)
Relative humidity change rate	±1%/h (±4%/8h)

* The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



Accessories

MediaBox
RFID Tags
Antivibration Tables
Adapters for Pipettes Calibration
Power Adapters
Protective cover for balances
RS 232, RS 485 cables
Density determination KIT
Additional modules
Professional weighing table
Protective cover for balances
Barcode scanners

Automatic feeders
USB Hubs
Label Printers
RS 232, RS 485 cables
THBR 2.0 System - Ambient Conditions Monitoring
Under-pan weighing
Anti-Draft Chamber for XA 4Y and XA 5Y Balances
Weighing dishes
Receipt Printer
Fingerprint Reader
RS 232 – USB Converter
Under-pan weighing

Software

RAD-KEY
Label Editor R02
R-LAB
RADWAG Development Studio

LabVIEW Driver
RADWAG Remote Desktop
Scales Editor 2.1
R.Barcode

Device dimensions

XA 52.5Y.A Analytical Balance

